

# SAHCO

1831



## Saji

Type: Upholstery

Composition: 78% recycled polyester, 22% nylon

Yarn type: Filament

Binding: Jacquard

Width: Approx. 140 cm, 55 inches

Weight: Approx. 480 g/lin.m, 15.5 oz/ly

Repeat: Approx. 11 cm, 4.5 inches V / 16 cm, 6.5 inches H

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week.

Remove stains as soon as they occur, with clean warm water or sparkling water. Extraction clean when necessary. Extraction cleaning might dissolve water based glue. Pay attention to temperature and amount of cleaning fluid. Washable at 30°C if loose covers. Drip drying. Mount in moist condition.

Disinfection, see [www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)



10 year warranty



### Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

*Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention*

### Pilling

Note 5, EN ISO 12945

### Seam slippage

Seam parallel to warp: 3.0 mm

parallel to weft: 3.5 mm

EN ISO 13 936-2 180 Newton

### Lightfastness

Note 5-6 ISO 105-B02

### Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

### Flame resistance

BS 5852 Crib 5 with treatment \*

BS 5852 part 1 with treatment \*

EN 1021-1/2

US Cal. Tech. Bull. 117

Free from added flame retardant chemicals as standard

*\* To pass this test flame retardant treatment is necessary.*

*We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

# SAHCO

1831

## **ACT Guidelines Woven fabrics**

Italy

## **Flammability**

US Cal. Bull. 117-2013

## **Launch**

2023

## **Dry & Wet Crocking AATCC 8**

Dry Crocking: Grade 5.0

Wet Crocking: Grade 4,5

## **Warranty**

10 years. See terms and conditions on kvadrat.dk

## **Colour Fastness to Light AATCC 16**

Grade 4-5 minimum 40 hours

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

## **Physical properties**

Pilling ASTM D3511 Class 5

Breaking Strength ASTM D5034 warp 98 / weft 308 lbs

Seam Slippage ASTM D4034 warp 32.5 / weft 105 lbs

For further information

[www.kvadrat.dk/en/sahco](http://www.kvadrat.dk/en/sahco)

## **Abrasion ASTM D4966**

45.000 cycles Martaindale – High Traffic

## **Environmental benefits**

Follow the EU Ecolabel dye restrictions incl. AZO dye  
and heavy metal restrictions

REACH compliant

Californian Proposition 65 list compliant

LBC Red list compliant

## **Green building certificates**

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA  
following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content and  
substance

## **Country of origin**